DSS SERIES

DSS

DGS

MEDIUM-WAVE ELECTRIC INFRARED HEATER

MW



Designer Series

Decorative option for heating high-end patios and outdoor areas by providing spot, total, or comfort heat.

Outdoor approved DSS Series heaters produce medium-wave, instant heat with the use of new technology, carbon lamps encased in a IP55 rated, compact, slim, black enclosure. This heater offers a remote control with timer functionality and four power settings. Operational benefits include a highly efficient energy transfer, even heat distribution, and intense heat output.



BENEFITS OF HEATING WITH ELECTRIC INFRARED

- Superior Comfort
- Reduced Energy Consumption
- Durability
- Even Heat Distribution
- Outdoor Tested & Approved
- Long Lamp Life Expectancy

PRODUCT FEATURES

AN-HERRY IN

- IP55 Design for Outdoor Use
- Remote Control with 4 Power Settings

• High Efficiency Carbon Lamps

- Compact, Slim Design
- Instant Heat
- Overheat & Tip Over Protection

DSS SERIES MEDIUM-WAVE ELECTRIC INFRARED HEATER

PRODUCT SPECIFICATIONS



Electrical Consumption: From 1,500 to 2,500 watts



Equivalent BTU: 5,118 to 8,530 BTU/h



Length: 34.5"L x 7.7"W x 3.3"H

Lamp Elements: Carbon

Certifications & Approvals: ETL Listed, Commercial/Industrial, Outdoor Residential



Limited Warranty: All Components - 1 year



Electrical: 120V or 230V

AVAILABLE DSS MODELS & CLEARANCES

| MODEL # | HOUSING COLOR | WATTS | VOLTAGE | AMPS | BTU'S | MOUNTING HEIGHTS ¹ | | MOUNTING ANGLE | SIDE | ТОР | BELOW |
|--------------|------------------|-------|---------|-------|-------|----------------------------------|----------------------------|-------------------|------|-----|-------|
| DSS-35B1-A15 | Black | 1,500 | 120 | 12.5 | 5,118 | 7' to 9' | VCES TO STIBLES HES) | 0 ° | 13" | 4" | 50" |
| DSS-35B1-C25 | Black | 2,500 | 230 | 10.87 | 8,530 | 8' to 12' | CLEARAI COMBUS (INCI | 0 ° | 13" | 4" | 50" |

² Factory recommended mounting heights are provided as a guideline. Actual conditions may dictate variations from the above data.

³ Refer to DSS Manual for additional information about clearances for 45° Mounting Angle.


Always maintain the published clearances to combustibles. Clearances published in DSS Series manual and on warning label supersede data shown on this brochure.



END -



END VIEW 0° - Mounting Angle







21400 Hoover Road, Warren, Michigan 48089 USA +1.586.756.0950 | sales@drp-co.com www.REVERBERRAY.com



