LYTValue Series A



INDUSTRIAL LED LIGHTING

High and Low-Bay LED Lighting



Cut down on energy costs with our LYTValue Series. This LED allows you to focus light where it is needed in commercial and industrial applications. This compact LED fixture allows for various mounting options and has been designed with durability in mind.

PRODUCT FEATURES

- Rugged aluminum housing
- Multiple mounting options
- · Shock and vibration resistant

BENEFITS OF LED BAY LIGHTING

- Reduced Energy Consumption
- Long Life Expectancy
- Maintenace Free
- Durability
- Instant On No Warm-Up Period
- Superior Light Quality
- High Efficiency

LYTValue Series A

High and Low-Bay LED Lighting

Product Specifications



Electrical:

Input Voltage: 110 to 277 VAC Input Frequency: 60 Hertz



Photometric:

Lumens: 8,600 Wattage: 97 watts

Color Temperature (CCT): 5,000K



Rated Life: 50,000 hours



Mounting: Suspended



Housing:

IP65 rated moisture resistance enclosure. Black powdercoat standard



Certifications:

UL



Limited Warranty:

5 year

Available LYTValue High and Low-Bay LED Lighting Models


MODEL#	APPLICATION Type	TYP. MOUNTING HEIGHTS	LUMENS	WATTS @ 277VAC	LUMENS /WATT	CRI	BEAM ANGLE	WEIGHT	
LYTV-A086	Low/High-Bay	12' to 20'	8,600	97	89	72	80°	5 lbs	_


Aluminum heavy duty housing; AC direct circuit board

This Re-Verber-LYT LED lighting fixture must be installed correctly. The contractor, owner, installer, purchaser, and user is responsible for installing, maintaining, and operating the light fixture in compliance with all state and local laws, ordinances, regulations, and the American National Standards Institute (ANSI) Safety Code.

The validity of the product warranty is subject to the correct storage, installation, operation, and maintenance of this product. Failing to comply with proper storage, installation, operation, and maintenance routines will make the warranty invalid. Specifications subject to change without notice.

Dimensions









21400 Hoover Road, Warren, Michigan 48089 USA +1.586.756.0950 | sales@drp-co.com









